

Valves (Wheel Operated) Double Spindle (JV-045-00)

Sr.No.	Gas Service	Wheel Operated	Inlet Thread Size * (As per customer requirement)						Outlet Thread Size	Working Pressure Bar	Hydraulic Test Pressure Bar
1	Oxygen	Wheel Operated	* 1/2"	17E	* 3/4"	* 25E	* 1"	* M18X1.5	W 21.8 Din 477 No.6	230	345

Valve (Material of Construction) JV-045-00

Sr.No.	Description	Material	Specification
1	Body	HT Brass	IS: 3224
2	Filter Assembly	-----	-----
3	Soft Seat	Nylon (PA66)	-----
4	Spindle 1	Free Cutting Brass	IS: 319
5	Spindle 2	Free Cutting Brass	IS: 319
6	Sleeve	Nylon	-----
7	"O" Ring	Neoperene / Nitrile Rubber	-----
8	Back up Ring	Teflon / Nylon	-----
9	"O" Ring	Neoperene / Nitrile Rubber	-----
10	Gland Plug	Free Cutting Brass	IS: 319
11	Knob	ABS	-----
12	Spacer	Mild Steel	-----
13	Cap (Knob)	ABS/Nylon	-----
14	Screw (Type-1,Cross recess)	Steel	-----