

Valves (Wheel Operated) Double Spindle (JV-064-00)

Sr.No.	Gas Service	Wheel Operated	Inlet Thread Size * (As per customer requirement)						Outlet Thread Size	Working Pressure Bar	Hydraulic Test Pressure Bar
1	Air	Wheel Operated	* 1/2"	17E	* 3/4"	* 25E	* 1"	* M18X1.5	G5/8"X 14 BSP	300	450

Valve (Material of Construction) JV-064-00

Sr.No.	Description	Material	Specification
1	Body	HT Brass	IS:3224
2	Soft Seat	Nylon (PA66)	-----
3	Spindle I	Free Cutting Brass	IS:319
4	Spindle II	Free Cutting Brass	IS:319
5	Sleeve	Nylon	-----
6	"O" Ring	Neoprene / Nitrila Rubber	-----
7	Back up Ring	Nylon / Teflon	-----
8	Gland Plug	Free Cutting Brass	IS:319
9	Knob Assembly	As per Drowing	-----
10	Cap (Knob)	ABS/Nylon	-----
11	Safety Plug	Free Cutting Brass	IS:319
12	Brusting Disc	Copper/SS/Nickel	-----
13	Safety Washer	Copper	-----
14	Siphon Tube with NRV Assembly	As per Drowing	-----
15	Pressure Gauge Washer	Copper	-----
16	Pressure Gauge	-----	-----
17	Locking Nut	MS (Chrome Plated)	-----
18	"O" Ring	Neoprene / Nitrila Rubber	-----