

Valves (Wheel Operated) Double Spindle (JV-085-00)

Sr.No.	Gas Service	Wheel Operated	Inlet Thread Size * (As per customer requirement)						Outlet Thread Size	Working Pressure Bar	Hydraulic Test Pressure Bar
1	Oxygen	Wheel Operated	* 1/2"	17E	* 3/4"	* 25E	* 1"	* M18X1.5	G3/4"	300	450

Valve (Material of Construction) JV-085-00

Sr.No.	Description	Material	Specification
1	Body	HT Brass	IS: 3224
2	Seat	Nylon (PA66)	-----
3	Seat Holder	Free Cutting Brass	IS: 319
4	Connecting Rod	Free Cutting Brass	IS: 319
5	Pressure Plate	Free Cutting Brass	IS: 319
6	"O" Ring	Neoperene / Nitrile Rubber	-----
7	Sealing Washer	Nylon	-----
8	Seat	Nylon	-----
9	"O" Ring	Neoperene / Nitrile Rubber	-----
10	Washer	Nylon	
11	Pressure Plate	Free Cutting Brass	IS: 319
12	Gland Nut	Free Cutting Brass	IS: 319
13	Washer	Nylon	-----
14	Spindle	Free Cutting Brass	IS: 319
15	"O" Ring	Neoperene / Nitrile Rubber	-----
16	Hand wheel	MS	-----
17	Locking nut	MS (Chrome Plate)	-----